

Lithium Complex Grease

Product Description

Thickened by complex soap, it is made from deeply refined mineral oil with various high performance additives through special technical process

Applications

The product is suitable for lubricating in some industry

Features

- Suitable for centralized lubricating system of rolling mill and rolling mill bearing in metallurgical industry. It can be used for lubricating bearing in mine industry, machinery etc.
- Be widely used for the lubrication of equipments and automobile in mine and other industry
- Application temperature range : 20°C ~ 180°C
- Use method : grease gun, hand grease, centralized lubricating grease
- It can remain on spot at friction pairs under high temperature
- It can lubricate and protect the equipment under water. Keep acceptable consistency in the process of using avoid being washed away
- Excellent oxidation resistant performance. Ensure longer service life during application process

Product Classification and Product Standard

- ISO 6743-9(GB 7631.8-90) : L-XBFHB 1, L-XBFHB 2, L-XBFHB 3.
- Q/SY RH2151
- 15kg/barrel, 175kg/barrel

Storage and Handling

- All storage equipments, tanks, pipes, valves and etc. apparatus has to be cleaned thoroughly and inspected to be clean for use before being used to transfer or transport KunLun Marine Lithium Complex Grease to prevent contamination.
- KunLun Marine Lithium Complex Grease must be stored in dedicated storage tanks/equipment and is recommended to be stored in an indoor and controlled environment.
- Storage tanks/equipment must be waterproof, mist-proof and free from other mechanical particles.
- Product must be labeled clearly and properly during the entire transportation process to prevent mixing of other petrol-chemical product into the Lithium Complex Grease.